



CENTERLINE STRIPING

NOTES:

1. * RCP PIPE UNDER 6FT WALKWAY TO HAVE MIN. 36FT LENGTH AND MIN. 15" DIA. WITH 2FT SHOULDER ON BOTH ENDS OF SIDEWALK.
2. ** BUFFER DISTANCE TO BE REGULATED BY POSTED SPEED LIMIT AS FOLLOWS:
 - 6FT BUFFER FOR 45 MPH POSTED SPEED
 - 5FT BUFFER FOR 35 MPH POSTED SPEED
 - 3FT BUFFER FOR 25 MPH POSTED SPEED
3. *** VARIABLE DISTANCE OF 3FT TO 6FT FROM BACK OF CURB TO FRONT OF SIDEWALK.
4. EXISTING ROADWAY TO BE SAW CUT TO REMOVE THE EXISTING EDGE LINE AND PROVIDE A SMOOTH TIE IN TO THE PROPOSED CURB AND GUTTER.
5. BUS SHELTERS WITHIN NCDOT R/W MUST FOLLOW THE NCDOT BUS SHELTER AND STOP GUIDELINES.

NOT TO SCALE



**TYPICAL CK RIDER
BUS STOP DETAIL**

SEPTEMBER 2022

415